

## Technical Specifications

### Mechanical

<b>Dimensions</b>	442.4 x 399.6 x 43.7 mm (17.4 x 15.7 x 1.7")
<b>Weight</b>	Without mounting brackets: 6.2 kg (13.7 lb) With mounting brackets: 6.3 kg (13.9 lb)
<b>Enclosure material</b>	SGCC steel

### Hardware

<b>Management interface</b>	Ethernet In-Band
<b>Networking interface</b>	(32) GbE RJ45 ports (16) 1/2.5 GbE RJ45 ports (4) 10G SFP+ ports
<b>PoE interface</b>	(32) PoE/PoE+ (Pins 1, 2+; 3, 6-) (16) 60W PoE++ (Pair A 1, 2+; 3, 6-) (Pair B 4, 5+; 7, 8-)
<b>Total non-blocking throughput</b>	112 Gbps
<b>Switching capacity</b>	224 Gbps
<b>Power method</b>	Universal input, 100—240V AC, 50/60 Hz USP RPS DC input
<b>Power supply</b>	AC/DC, internal
<b>Supported voltage range</b>	100—240V AC
<b>Total available PoE</b>	720W
<b>Max. PoE wattage per port by PSE</b>	PoE: 15.4W PoE+: 30W PoE++: 60W
<b>Voltage range PoE mode</b>	PoE: 44—57V PoE+: 50—57V
<b>LCM display</b>	(1) 1.3" touchscreen
<b>Button</b>	Factory reset
<b>Operating temperature</b>	-5 to 40° C (23 to 104° F)
<b>Operating humidity</b>	10 to 90% noncondensing
<b>Certifications</b>	CE, FCC, IC

### Etherlighting

<b>Ethernet</b>	Locating Speed/link VLAN
<b>SFP+</b>	Locating Speed/link VLAN
<b>LEDs</b>	
<b>System</b>	Status
<b>RPS</b>	Status